Printing date 12.12.2019 Version: 3 Revision: 12.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: CLEANSOLV HE (Listed NSF K1, K3: n° 151567)
- · Article number: 98690001
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- · Product category PC35 Washing and cleaning products (including solvent based products)
- Process category

PROC7 Industrial spraying PROC11 Non industrial spraying

- · Application of the substance / the mixture Industrial cleaner
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

ZEP UK Ltd

Tanhouse Lane

Widnes Cheshire, WA8 0RD

United Kingdom

Tel: +44 (0)151 422 1000 Fax: +44 (0)151 422 1011 @: info@zep.co.uk web: www.zep.co.uk

ZEP Industries BV

Vierlinghweg 30

4612 PN Bergen op Zoom

The Netherlands

Tel: (NL) + 31 164 250 100 (B) + 32 2 347 0117 Fax:(NL) + 31 164 266 710 (B) + 32 2 347 1395

@: sales@zepbenelux.com

ZEP ITALIA SRL

Via Netunese Km. 25.000

04011 Aprilia (LT) - Italy

Tel: +39.06.926691 Fax: +39.06.92747061

@: tecnico@zepeurope.com

Sito: www.zep.it

· Further information obtainable from:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· 1.4 Emergency telephone number:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

EU: Tel. 112

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. (Contd. on page 2)

Printing date 12.12.2019 Revision: 12.12.2019 Version: 3

Trade name: CLEANSOLV HE (Listed NSF K1, K3: n° 151567)

· Hazard pictograms

(Contd. of page 1)







· Signal word Danger

Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light propan-2-ol

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EC number: 921-024-6	Naphtha (petroleum), hydrotreated light	
Reg.nr.: 01-2119475514-35-xxxx	 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336 	
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol	5-10%
CAS: 124-38-9 EINECS: 204-696-9	carbon dioxide ♦ Press. Gas R, H281	2.5-5%

Ingredients according to Detergents Regulation 648/2004/EC

For the wording of the listed hazard phrases refer to section 16.

Aliphatic hydrocarbons	≥30%
ISOPROPYL ALCOHOL	≥5 - <15%

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

- · After swallowing: Seek immediate medical advice.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Printing date 12.12.2019 Version: 3 Revision: 12.12.2019

Trade name: CLEANSOLV HE (Listed NSF K1, K3: n° 151567)

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:		
67-63-0 propan-2-ol (5	-10%)	
WEL (Great Britain) Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm		
124-38-9 carbon dioxid	le (2.5-5%)	
WEL (Great Britain)	Short-term value: 27400 mg/m³, 15000 ppm Long-term value: 9150 mg/m³, 5000 ppm	
	(Contd. on r	nage 4

Printing date 12.12.2019 Version: 3 Revision: 12.12.2019

Trade name: CLEANSOLV HE (Listed NSF K1, K3: n° 151567)

			(Contd. of page
IOELV (Ει	uropean Union) Lor	ig-term value: 9	9000 mg/m³, 5000 ppm
DNELs			
67-63-0 pr	opan-2-ol		
Oral	DNEL Long term-s	ystemic	26 mg/kg human/day (consumer)
Dermal	DNEL Long term-s	ystemic	319 mg/kg human/day (consumer)
			888 mg/kg human/day (worker)
Inhalative	DNEL Long term-s	ystemic mg/m3	89 mg/m3 (consumer)
			500 mg/m3 (worker)
PNECs			
67-63-0 pr	opan-2-ol		
PNEC Fre	shwater mg/L	140.9 mg/L	
PNEC Marinewater mg/L 140.9 mg/L		140.9 mg/L	
PNEC Freshwater sediment 552 mg/Kg		552 mg/Kg	
PNEC Marine water sediment 552 mg/Kg		552 mg/Kg	
PNEC Intermittent release 140.9		140.9	
PNEC Soil 28 mg/Kg		28 mg/Kg	

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- Respiratory protection: Filter A
- · Protection of hands:



Protective gloves

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· Not suitable are gloves made of the following materials: Strong material gloves

Not determined.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol
Colour: Colourless
Odour: Characteristic
Odour threshold: Not determined.

· pH-value:

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 80 °C

· Flash point: <0 °C

(Contd. on page 5)

Printing date 12.12.2019 Version: 3 Revision: 12.12.2019

Trade name: CLEANSOLV HE (Listed NSF K1, K3: n° 151567)

	(Contd. of page
Flammability (solid, gas):	Not applicable.
Ignition temperature:	425 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	0.747 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Insoluble.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	96.5 %
EU-VOC:	720.9 g/l
EU-VOC	96.50 %
Swiss VOC:	96.50 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

	LD/LC50 values relevant for classification:		
Naphtha (j	petroleum), h	ydrotreated light	
Oral	LD50	>2,000 mg/kg (Rat)	
Dermal	LD50	>2,000 mg/kg (Rat)	
Inhalative	LC50 / 4 h	>20 mg/l (Rat)	
	LC50	10-100 mg/l (Selenastrum capricornutum (Algae))	
		1-10 mg/l (fish)	
67-63-0 pr	opan-2-ol		
Oral	LD50	>5,000 mg/kg (Rat)	
Dermal	LD50	6,290 mg/kg (rab)	
Inhalative	LC50 / 4 h	46-73 mg/l (Rat)	
	LC50/8 h	12,000-19,000 mg/m3 (Rat)	
	LC50 / 96 h	9,640 mg/ltr (fish)	

(Contd. on page 6)

Printing date 12.12.2019 Version: 3 Revision: 12.12.2019

Trade name: CLEANSOLV HE (Listed NSF K1, K3: n° 151567)

Contd. of page 5)

>1,400 mg/ltr (Lepomus gobbosus (Zonnebaars))

6,550 mg/ltr (Pimephales promelas)

EC50 / 24 h >1,000 mg/ltr (Daphnia magna (water flea))

EC 50 / 48 h 2,285-13,299 mg/ltr (Daphnia magna (water flea))

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations

- · Uncleaned packaging:
- · Recommendation: Disposal in accordance with administrative provisions

SECTION 14: Tr	ansport i	nformat	ion
----------------	-----------	---------	-----

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS (Naphtha (petroleum), hydrotreated light), MARINE POLLUTANT
· IATA	AEROSOLS, flammable

(Contd. on page 7)

Printing date 12.12.2019 Version: 3 Revision: 12.12.2019

Trade name: CLEANSOLV HE (Listed NSF K1, K3: n° 151567)

	(Contd. of pag
14.3 Transport hazard class(es)	
ADR	
Class Label	2 5F Gases. 2.1
IMDG	
Class Label	2.1 2.1
IATA	
Class Label	2.1 2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Product contains environmentally hazardous substances:
Marine pollutant:	Naphtha (petroleum), hydrotreated light Yes
Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number: Stowage Code	F-D,S-U SW1 Protected from sources of heat.
Slowage Code	SW22 For AEROSOLS with a maximum capacity of 1 litre:
	Category A. For AEROSOLS with a capacity above 1 litre:
	Category B. For WASTE AEROSOLS: Category C, Clear of
Segregation Code	living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre:
2-66	Segregation as for class 9. Stow "separated from" class 1 exce
	for division 1.4.
	For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Annex II of the IBC Code	f Marpol and Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL Code: F0
Excepted quantities (E Q)	Code: E0 Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
	(Contd. on page

Printing date 12.12.2019 Version: 3 Revision: 12.12.2019

Trade name: CLEANSOLV HE (Listed NSF K1, K3: n° 151567)

(Contd. of page 7)

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Reg. (EC) n. 1272/2008 - CLP;

Reg. (EC) n. 1907/2006 – Reach;

Reg. (EC) n. 2015/830 annex II of REACH;

Reg. (EC) n. 648/04 (Detergents);

Reg. (EC) n. 528/12 (Biocides BPR);

Reg. (EC) n. 1223/2009 (Cosmetics);

Dir. 06/08 ADR - RID - IMDG - IATA;

Dir. 47/08 (Aerosols); Dir. 12/18 (Seveso III);

Dir. 2008/98/CE and Reg. (EC) n.1357/2014 (Waste management)

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P3b FLAMMABLE AEROSOLS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	75-100

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H281 Contains refrigerated gas; may cause cryogenic burns or injury.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

Contact:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395 IT: Tel: +39 069 266 91Fax: +39 06.927 470 61 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)

Printing date 12.12.2019 Revision: 12.12.2019 Version: 3

Trade name: CLEANSOLV HE (Listed NSF K1, K3: n° 151567)

(Contd. of page 8)

CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Aerosol 1: Aerosols - Category 1

Press. Gas R: Gases under pressure – Refrigerated liquefied gas Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
* Data compared to the previous version altered.

(Contd. on page 10)

Printing date 12.12.2019 Version: 3 Revision: 12.12.2019

Trade name: CLEANSOLV HE (Listed NSF K1, K3: n° 151567)

(Contd. of page 9)

Annex: Exposure scenario

· Short title of the exposure scenario

For the finished product.

CLEANSOLV HE (Listed NSF K1, K3: n° 151567)

- · Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- Product category PC35 Washing and cleaning products (including solvent based products)
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Aerosol
- · Concentration of the substance in the mixture The substance is main component.
- · Used amount per time or activity According to directions for use.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure Use only on hard ground.
- Other operational conditions affecting worker exposure

Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- · Other operational conditions affecting consumer exposure Keep out of the reach of children.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- Technical protective measures

Provide explosion-proof electrical equipment.

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

Avoid contact with the skin.

Protective gloves

· Measures for consumer protection

Ensure adequate labelling.

Keep locked up and out of the reach of children.

- · Environmental protection measures
- · Water Do not allow to reach sewage system.
- · Soil Prevent contamination of soil.
- Disposal measures

Disposal in accordance with administrative provisions

Ensure that waste is collected and contained.

- Disposal procedures Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

GB